

POLEAS VARIADORAS - TD

Modelo	Clave	Potencia Admitida	Relacion Variacion	Medida Eje 1	Correa a utilizar	Reactor
	TD - 02 FG - 100 FUNDICION GRIS	0.25 HP a 0.75 HP	2:1	Ø 27 LARGO 90 mm.	V- SECCION A-	RESORTE 1
	TD - 02 FG 2 150	0.50 HP a 1.50 HP	3:1 55-150	Ø 35 LARGO 100 mm.	V - A HASTA 24 mm.	RESORTE 1
	TD - 02 FG 3 190	1 a 3 HP	3.50:1 55-150	Ø 40 mm. LARGO 115 mm.	V - B HASTA 40 mm.	RESORTE 1
	TD - 02 FG 3 230	1.5 HP a 5 HP	3.53:1 65-230	Ø 45 LARGO 125 mm.	TRAPECIO 26 mm. HASTA 45 mm.	RESORTE 1
	TD - 02 FG 3 270	2 HP a 7 HP	3.60:1 75-270	Ø 50 LARGO 130 mm.	TRAPECIO 38 mm. HASTA 57 mm.	RESORTE 1
	TD - 02 FG 3 350	3 HP a 12 HP	3.90:1 80-350	Ø 60-70 LARGO 140 mm.	TRAPECIO 45 mm. HASTA 75 mm.	RESORTE 1
	TD - 03 FG 3 150 2RS	0.50 HP a 1.50 HP	3:1 55-150	Ø 35 LARGO 130 mm.	V - A HASTA 24 mm.	RESORTE 2
	TD - 03 FG 3 190 2RS	1 HP a 3 HP	3.50:1 55-193	Ø 40 LARGO 133 mm.	V - B HASTA 40 mm.	RESORTE 2
	TD - 03 FG 3 230 2RS	1.5 HP a 5 HP	3.53:1 65-230	Ø 45 LARGO 140 mm.	TRAPECIO 26 mm. HASTA 45 mm.	RESORTE 2
	TD - 03 FG 3 270 2RS	2 HP a 7 HP	3.60:1 75-270	Ø 50 LARGO 145 mm.	TRAPECIO 28 mm. HASTA 57 mm.	RESORTE 2
	TD - 03 FG 6 350 2RS	3 HP a 12/15/20 HP	3.90:1 85-350	Ø 60-70 LARGO 175 mm.	TRAPECIO 45 mm. HASTA 75 mm.	RESORTE 2
	TD-BM M 12 F G	0.50 HP a 2 HP	350 mm.	ANCHO 200 mm.	Ø GUIAS 16 mm.	ROSCA 1/2" W.
	TD-BM M 16 F G	2 HP a 5 HP	550 mm.	ANCHO 300 mm.	Ø GUIAS 25 mm.	ROSCA 1" W.
	TD-BM M 20 F G	5 HP a 12 HP	650 a 750 mm.	ANCHO 400 mm.	Ø GUIAS 35/40 mm.	ROSCA 1 1/4" mm a 1 1/2" mm

TRANSMISIONES INDUSTRIALES ALFA

Av. Pte Peron 2811, San Justo (1754), Bs.As

E-mail: alfa_transmisiones@hotmail.com

Tel/Fax: 011 4651-5008 / 011 4484-1705

www.transmisionesalfa.com.ar